



Product Specification Sheet

(Issue 1.0)

Product Name:

25mm hydrophobic high performance microfibre sound and heat insulation.

Product Description:

A high performance quality acoustic and thermal insulation material. Ideal for airborne noise absorption in both wet and dry applications



Tolerance

Composition: Mixed PES and PP Fibers

± 2%

Colour: White

N/A

Weight: 400g /m²

± 10%

Thickness: 25mm (Nominal)

± 4mm

Typical Temperature Stability: -20°C to +100°C

± 10%

Available Sizes: 1m wide : up to 10m long

± 5%

Applicable Vehicle Areas:

Applicable Applications:

	Interior	Exterior	Underbody	Engine Bay
Interior:	Tunnel	Dash	Floor	Roof
Interior:	Wheelarch	Loadspace	Pillars	Body
Exterior:	Wheelarch	Bumpers	Outer dash	Exhaust
Underbody:	Tunnel	Underfloor	Undertray	Transmission
Engine Bay:	Engine	Engine cover	Outer dash	Exhaust

* Recommended check application temp.

The data in this product specification sheet is provided in good faith, however this information should only be used as a guide and not be used to determine a final product specification nor suitability for a specific application. It is the customers responsibility to ensure adequate performance testing is carried out prior to fitting any Campervan Insulation UK products into any application.



Lux Distribution Ltd
(trading as Car Insulation UK)
2 & 3 Rugby House, Hinckley Rd, Sapcote, LE9 4FS.
Company No. VAT No.
E: info@carinsulation.co.uk T: 01455 272921

