



Indoor Units for Multi Split

Model (Indoor)			A16EW4H4R09	A16EW4H4R12	A16EW4H4R18
Power Supply	Rated Voltage	V	208/230	208/230	208/230
	Rated Frequency	Hz	60Hz	60Hz	60Hz
	Phases		1	1	1
Cooling Capacity		Btu/h	9,000	12,000	18,000
Heating Capacity		Btu/h	9,000	13,000	19,800
Air Flow Volume(SH/H/M/L)		CFM	330/294/253/218	341/277/253/218	500/459/383/324
Dehumidifying Volume		L/h	0.8	1.4	1.8
Application Area		ft ²	129 to 194	172 - 258	247 - 365
Sound Pressure Level (SH/H/M/L)		dB (A)	41/37/35/26	42/38/36/28	46/44/40/35/-
Sound Power Level (SH/H/M/L)		dB (A)	51/47/45/36	52/48/46/38	56/54/50/45/-
Dimension (WxHxD)		in	33.39 x 10.83 x 7.09	33.39 x 10.83 x 7.09	37 x 11.73 x 7.87
Dimension of Package (WxHxD)		in	36.14 x 14.57 x 10.16	36.14 x 14.57 x 10.16	39.88 x 11.34 x 15.55
Net Weight		lbs	22	22	28.6
Gross Weight		lbs	28.6	28.6	37.4
Connection Pipe	Outer Diameter Liquid Pipe	in	φ 0.24	φ 0.24	φ 0.24
	Outer Diameter Gas Pipe	in	φ 0.375 (3/8)	φ 0.375 (3/8)	φ 0.47