



# Slim Duct

Slim Duct Indoor Unit			CH-09MSPHDT-230VI	CH-12MSPHDT-230VI	CH-18MSPHDT-230VI	CH-24MSPHDT-230VI
Cooling Capacity		BTU/h	9,000	12,000	18,000	24,000
Power supply		V,Hz,Ph	208-230,60,1	208-230,60,1	208-230,60,1	208-230,60,1
Minmum circuit ampacity		A	1,2	1.3	1.9	2,5
Max.fuse		A	15	15	15	15
Indoor air flow (Hi/Med/Lo) (No duct)		CFM	335/290/240	370/320/260	520/430/360	820/620/520
Indoor noise level (Hi/Med/Lo) ( Standard pressure )		dB(A)	39/37/33	40/38/33	36/34/30	50/46/45
Indoor unit	Dimension (WxDxH)(body)	inch	27.56x25x8.27	27.56x25x8.27	36.22x25x8.27	36.22x25x10.63
	Packing (WxDxH)(body)	inch	36.02x25.79x11.42	36.02x25.79x11.42	44.68x25.79x11.42	44.68x25.79x13.78
	Net/Gross weight(body)	lb	39.90/50.27	39.90/50.27	50.7/63.93	57.32/68.34
Refrigerant piping	Liquid side/ Gas side	inch	1/4"/3/8"	1/4"/1/2"	1/4"/1/2"	3/8"/5/8"
Controller			Remote/Wired control	Remote/Wired control	Remote/Wired control	Remote/Wired control
Cooling		°F	62~90	62~90	62~90	62~90
Heating		°F	32~86	32~86	32~86	32~86
Operation temperature		°F	62~86	62~86	62~86	62~86
Qty/per 20' /40' /40'HQ			173/340/380	173/340/380	134/270/310	110/230/260