

Outdoor Unit Single Zone Heat Pump Ductless System

Outdoor Model: DLCSRBH06AAK

Submittal Data

Job Data: Location:

Buyer: Buyer P.O. #: Carrier #:

Unit Number: Model Number:

Performance Data Certified By: Date:



STANDARD FEATURES

- Variable Speed (Inverter)
- Factory installed Base Pan Heater
- Factory installed Crankcase Heater
- Low Voltage Controls
- Auto-Restart function
- Condenser High Temp Protection
- Modes: Cool, Heat, Dry, Fan, Auto
- Quiet operation
- Anti-corrosive fin coating



NOTE: Images for illustration purposes only. Actual models may be slightly different.

System	Size	6	
	Outdoor Model	DLCSRBH06AAK	
Electrical	Voltage, Phase, Cycle	V/Ph/Hz	208/230-1-60
	MCA	A.	13
	Recommended Fuse Size	A.	15
Operating Range	MOCP - Fuse Rating	A.	15
	Cooling Outdoor DB Min - Max	°F(°C)	-22~130 (-30~55)
	Heating Outdoor DB Min - Max	°F(°C)	-22~86 (-30~30)
Piping	Total Piping Length	ft (m)	82 (25)
	Piping Lift	ft (m)	32 (10)
	Pipe Connection Size - Liquid	in (mm)	1/4 (6.35)
	Pipe Connection Size - Suction	in (mm)	3/8 (9.52)
Refrigerant	Refrigerant Type	R410A	
	Metering Device	EEV	
	Charge	lbs (kg)	2.38 (1.08)

Outdoor Coil	Face Area	Sq. Ft.	4.0
	No. Rows	2	
	Fins per inch	21	
	Circuits	4	
Compressor	Type	Rotary Inverter	
	Model	KSK103D33UEZ3	
	Oil Type	VG74	
	Oil Charge	Fl. Oz.	10.5
Outdoor	Rated Current	RLA	6.4
	Unit Width	in (mm)	30.12 (765)
Outdoor	Unit Height	in (mm)	21.85 (555)
	Unit Depth	in (mm)	11.93 (303)
	Net Weight	lbs (kg)	63.71 (28.9)
	Airflow	CFM	1,324
	Sound Pressure	dB(A)	54.5

* Condensing unit above or below indoor unit

See compatibility chart for additional model specific information

Performance

High Wall	Indoor Model		6K (208/230V)
	Energy Star		YES
	Cooling Rated Capacity	Btu/h	6,000
	Cooling Cap. Range Min - Max	Btu/h	2,490~11,000
	SEER		23.5
	EER		15
	Heating Rated Capacity (47°F)	Btu/h	7,000
	Heating Rated Capacity (17°F)	Btu/h	3,600
	Heating Maximum Capacity (17°F)	Btu/h	9,000
	Heating Maximum Capacity (5°F)	Btu/h	7,300
	Heating Cap. Range Min - Max	Btu/h	2,300~11,200
	HSPF		11.0
	COP (47°F)	W/W	3.76
	COP (17°F)	W/W	2.70
	COP (5°F)	W/W	1.90

Construction View

Outdoor Model:

DLCSRBH06AAK

