

# DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

**Nullifire**  
Smart Protection

No. FB750 – 20170703

1. **Unique identification code of the product-type:** Nullifire FB750 Intubatt

**Intended use/es:** A mineral wool board coated on both faces used to reinstate the fire resistance performance of wall constructions where they have been provided with apertures for the penetration of single or multiple services.

3. **Manufacturer:** TREMCO CPG UK Limited, Coupland Road, Hindley Green, Wigan. WN24HT

5. **System/s of AVCP:** System 1

6. **European Assessment Document:** ETAG 026 edition 2011 part 2

**European Technical Assessment:** ETA 17/0392

**Technical Assessment Body:** CPR Notified Body UL International UK Ltd, No. 0843

**Notified body/ies:** CPR Notified Body UL International UK Ltd, No. 0843

7. **Declared performance/s**

Basic Work Requirement	Performance
<b>Mechanical resistance and stability</b>	
None	Not relevant
<b>Safety in case of fire</b>	
Reaction to fire (EN 13501-1)	Class E
Resistance to fire (EN 13501-2)	See ETA17/0392 Annex A
<b>Hygiene, Health and the Environment</b>	
Air Permeability (EN 1026:2000)	See ETA17/0392 Annex B
Water Permeability (ETAG 026-2 Annex C)	NPD
Release of dangerous substances	Declaration of manufacturer – Uses categories IA3, S/W3
<b>Safety in Use</b>	
Mechanical Resistance and stability (EOTA TR001:2003)	NPD
Resistance to Impact / movement (EOTA TR001:2003)	NPD
Adhesion (EOTA TR001:2003)	NPD
<b>Protection against noise</b>	
Airborne Sound Insulation (EN10140-2 / EN ISO 717-1)	See ETA17/0392 Annex C
<b>Energy, Economy and Heat Retention</b>	
Thermal Properties (EN 12664, EN 12667 or EN 12939)	NPD
Water vapour permeability (EN ISO 12572 / EN 12086)	NPD
<b>General Aspects Relating to fitness for use</b>	
Durability and Serviceability (EOTA TR 024:2009)	Z <sub>1</sub>

NPD = No Performance Determined

# DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

**Nullifire**  
Smart Protection

## 8. Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

*M. Liptrot, Operations Director*



*At Wigan on 1 July 2020*

### **Annex:**

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.

# DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

**Nullifire**  
Smart Protection

2.

<b>CE</b>	
TREMCO CPG UK Limited Coupland Road, Hindley Green, Wigan, WN2 4HT 17 0843-CPR-0369 FB750 – 20170703 www.nullifire.com/FB750	
EN 1366 Part 3 ETA 17/0392 ETAG 26, Part 2	
A mineral wool board coated on both faces used to reinstate the fire resistance performance of wall constructions where they have been provided with apertures for the penetration of single or multiple services.	
<b>Essential Characteristic</b>	<b>Performance</b>
<b>Safety in Case of Fire</b>	
Reaction to fire	Class E
Resistance to fire	ETA 17/0392 Annex A
<b>Hygiene, Health and Environment</b>	
Air Permeability	ETA 17/0392 Annex B
Water Permeability	NPD
Dangerous Substances	Uses categories IA3, S/W3
<b>Safety in use</b>	
Mechanical resistance and stability	NPD
Resistance to impact/movement	NPD
Adhesion	NPD
<b>Protection against noise</b>	
Airborne sound insulation	ETA 17/0392 Annex C
<b>Energy, Economy and Heat Retention</b>	
Thermal properties	NPD
Water vapour permeability	NPD
<b>General aspects relating to fitness for use</b>	
Service & Durability	Z <sub>1</sub>